Shinland

Each Ray is brighter in Shinland

SL-044A

Details Matched LED Source

Material: URC2500 Cover Material: PC

Process: Vaccum Aluminum Plating PC

MAX Diameter: 44.0mm
Height: 20.2mm
Matched Holder: SL-HD-A

Matched Cover: SL-044-CLEAR-LENS/SL-044-MIXING-LENS

ROSH Compliant: YES
Status: Ready

Optical Properties

Code	Typ. FWHM	Typ. Eff	_ V6 C6
SL-04413A	13°	93%	Soleriq S8
SL-04425A	25°	93%	_
SL-04438A	38°	93%	

Photo LC010C

NJCxS024Z NJCxS024B

CLU700

BMC

CXM-6

CHM-6


CXM-7


CXA13







Dimensional Figure SL-044A
















Dimensional Figure SL-CXM-6-HD-A















Dimensional Figure SL-BRH-V8-HD-A













Dimensional Figure SL-CXA1304-HD-A












Distribution Curve Flux


SL-044A&SL-CXM-6-HD-A







SL-04413A K:3.06cd/lm,LED:CXM-6





SL-04425A K:3.06cd/lm,LED:CXM-6







SL-04438A K:3.06cd/lm,LED:CXM-6



Distribution Curve Flux

SL-04413A&SL-BRH-V8-HD-A







105° 105° cd/klm C0 - C180 -


- C90 - C270

SL-04413A K:2.67cd/lm,LED:V8





SL-04425A K:2.23cd/lm,LED:V8





SL-04438A K:1.28cd/lm,LED:V8




Distribution Curve Flux


SL-044A&SL-CXA1304-HD-A






SL-04413A K:4.84cd/lm,LED:CXA1304





105°
90°
90°
75°
75°
75°
60°
800
60°
1200
45°
1600
30°
15°
0°
15°
30°
2001

SL-04425A K:1.90cd/lm,LED:CXA1304



SL-04438A K:1.56cd/lm,LED:CXA1304



Package Description

SL-044A

PART N0.	WITHOUT PC COVER		WITH PC COVER		BOX SIZE
	Number Per Box (pcs)	Box Weigh (kg)	Number Per Box (pcs)	Box Weigh (kg)	(cm)
SL-04413A	750	4.25	700	5.53	55 X 32 X 32
SL-04425A	750	4.65	700	5.75	55 X 32 X 32
SL-04438A	750	4.20	700	5.95	55 X 32 X 32



Notes

- It is not allowed to scrub the reflective surface. If there is dust on the surface, please clean by soft cotton with little water.
- It is forbidden to clean with industrial solvent such as ethanol.
- Storage temperature: 0°C-40°C, and humidity:30%-95%
- Keep reflectors in package to void the dust.
- Prohibit the reflector touch with acid or alkaline solvent

About Shinland

Shenzhen Shinland Co. Ltd,one of the longest and most professional company in lighting optical field,have 20 years experience.Different from other factory which only have simple process, all aspects included R&D,making mold,injection molding ,vacuum coating and market support are our company own vertically integrated production .

Insisting on 'Quality First, Service First' and pragmatic, enterprising spirit, building the market by quality, casting our brand by credibility and integrity ,Shinland now become the leading supplier of lighting optical solution in China.

