# Shinland

Each Ray is brighter in Shinland

### SL-045B

#### Details

| Details         | LED Source                 |        |
|-----------------|----------------------------|--------|
| Material:       | URC2500                    | 000.00 |
| Cover Material: | PC                         |        |
| Process:        | Vaccum Aluminum Plating PC | CLL03x |
| MAX Diameter:   | 45.0mm                     | 540    |
| Height:         | 20.1mm                     | E13    |
| Matched Holder: | SL-HD-A                    |        |
| Matched Cover:  | WITHOUT                    | MEGA   |
| ROSH Compliant: | YES                        |        |
| Status:         | Ready                      | G17    |
|                 | -                          | C4     |

#### **Optical Properties**

| Code      | Typ. FWHM | Typ. Eff |  |
|-----------|-----------|----------|--|
| SL-04524B | 24°       | 91%      |  |
| SL-04550B | 50°       | 91%      |  |

| NVExJ048Z |
|-----------|
| NFCxJ108B |
| NFDxJ130B |

Matched


#### Photo








# Dimensional Figure SL-045B

Measure Unit: mm















### Dimensional Figure SL-CLL030-HD-A


Measure Unit: mm







#### **Distribution Curve Flux** SL-04524B&SL-CLL030-HD-A&Citizen 03x



K:1.33cd/lm,LED:CLL038

67.5° 90.09

67.5° 90.0°

Shinland

# Package Description

SL-045B

| PART N0.  | WITHOUT PC COVER |           | WITH PC COVER  |           | BOX SIZE    |
|-----------|------------------|-----------|----------------|-----------|-------------|
|           | Number Per Box   | Box Weigh | Number Per Box | Box Weigh | (cm)        |
|           | (pcs)            | (kg)      | (pcs)          | (kg)      |             |
| SL-04524B | 750              | 6. 10     | *              | *         | 55X 32 X 32 |
| SL-04550B | 750              | 4. 93     | *              | *         | 55X 32 X 32 |



#### Notes

- It is not allowed to scrub the reflective surface. If there is dust on the surface, please clean by soft cotton with little water.
- It is forbidden to clean with industrial solvent such as ethanol.
- Storage temperature: 0°C-40°C, and humidity:30%-95%
- Keep reflectors in package to void the dust.
- Prohibit the reflector touch with acid or alkaline solvent

# **About Shinland**

Shenzhen Shinland Co. Ltd,one of the longest and most professional company in lighting optical field,have 20 years experience.Different from other factory which only have simple process, all aspects included R&D,making mold,injection molding ,vacuum coating and market support are our company own vertically integrated production .

Insisting on 'Quality First, Service First' and pragmatic, enterprising spirit,building the market by quality, casting our brand by credibility and integrity ,Shinland now become the leading supplier of lighting optical solution in China.

